

Contents

CONTENTS	7
LIST OF FIGURES.....	10
1 INTRODUCTION.....	15
2 THE CRYSTALLINE SILICON THIN-FILM SOLAR CELL.....	17
2.1 THE LOW-TEMPERATURE APPROACH.....	18
2.2 THE HIGH-TEMPERATURE APPROACH	18
2.2.1 <i>General</i>	19
2.2.2 <i>Concepts of high-temperature CSiTF solar cells</i>	22
3 THE CSiTF SOLAR CELL ON FOREIGN SUBSTRATE	25
3.1 OVERVIEW OF THE PREPARATION STEPS.....	25
3.2 THE SUBSTRATE	26
3.3 DIFFUSION BARRIER LAYERS	27
3.4 SILICON DEPOSITION BY ATMOSPHERIC PRESSURE CVD	28
3.5 GRAIN ENLARGEMENT BY ZONE-MELTING RECRYSTALLISATION.....	29
3.6 CELL PROCESS FOR ONE-SIDE CONTACTED CSiTF SOLAR CELLS.....	30
3.7 MAIN TOPICS OF THIS RESEARCH WORK	31
3.7.1 <i>The intermediate layer as barrier against impurities</i>	32
3.7.2 <i>Zone-melting recrystallisation and solar cell processing</i>	34
4 DIFFUSION BARRIER PROPERTIES OF SILICON DIOXIDE AND SILICON NITRIDE INTERMEDIATE LAYERS.....	39
4.1 RELEVANT ASPECTS OF DIFFUSION.....	39
4.2 PREPARATION AND GENERAL PROPERTIES OF INTERMEDIATE LAYERS USED FOR CSiTF SOLAR CELLS	44
4.2.1 <i>Deposition of intermediate layers</i>	44
4.2.2 <i>Mechanical and chemical properties</i>	45
4.3 INVESTIGATED IMPURITY METALS.....	47
4.4 KNOWN DIFFUSION BARRIER PROPERTIES.....	48
4.4.1 <i>Properties of impurity diffusion in SiO₂</i>	48

4.4.2	<i>Properties of impurity diffusion in Si₃N₄</i>	49
4.4.3	<i>Properties of impurity diffusion in SiC</i>	52
4.5	OVERVIEW OF EXPERIMENTS DONE ON DIFFUSION BARRIER PROPERTIES	52
4.6	INDIRECT INVESTIGATION METHOD	54
4.6.1	<i>Investigations on metal – barrier – silicon structure</i>	54
4.6.2	<i>Investigations on metal – μc-silicon – barrier – silicon structures</i>	55
4.6.3	<i>Investigations on metal – silicon – barrier – Si structures</i>	59
4.7	THE DIRECT INVESTIGATION METHOD – ION IMPLANTATION	67
4.7.1	<i>Experimental approach</i>	67
4.7.2	<i>Experiment</i>	68
4.7.3	<i>Results and analysis</i>	70
4.8	APPLICATION OF DIFFUSION BARRIER RESULTS ON A TYPICAL MANUFACTURING PROCESS OF CSiTF SOLAR CELLS.....	73
4.8.1	<i>Simulation tool</i>	74
4.8.2	<i>Influence of uncertainties of experimental values</i>	75
4.8.3	<i>Influence of diffusivity in substrate</i>	76
4.8.4	<i>Influence of intermediate layer thickness</i>	77
4.9	SUMMARY	78
5	ZONE-MELTING RECRYSTALLISATION OF THIN SILICON LAYERS AND PREPARATION OF CSiTF SOLAR CELLS	81
5.1	EXPERIMENTAL SET-UP FOR ZONE-MELTING RECRYSTALLISATION	82
5.2	THE ONE-SIDE CONTACT SOLAR CELL PROCESS	85
5.3	MULTICRYSTALLINE SILICON WAFERS AS IDEAL SUBSTRATE	88
5.3.1	<i>Particularities of crystal growth using ZMR</i>	88
5.3.2	<i>Parameters influencing the supercooled zone</i>	91
5.3.3	<i>Influence of substrate base temperature</i>	93
5.3.4	<i>Influence of the intensity profile of the focussed lamp</i>	97
5.3.5	<i>CSiTF solar cells on optimised ZMR layers</i>	101
5.3.6	<i>Summary</i>	104
5.4	SSP RIBBON AS SUBSTRATE	104
5.4.1	<i>Preparation of the silicon layer</i>	105
5.4.2	<i>Solar cell results and electrical properties</i>	107
5.4.3	<i>Summary</i>	109
5.5	SILICON NITRIDE CERAMICS AS SUBSTRATE	110

5.5.1	<i>Sample structure and preparation</i>	110
5.5.2	<i>Crystallographic properties</i>	113
5.5.3	<i>Solar cell results and electric properties</i>	120
5.5.4	<i>Summary</i>	124
5.6	SILICON-INFILTRATED SILICON CARBIDE CERAMICS AS SUBSTRATE	126
5.6.1	<i>SiSiC substrates with SiO₂/SiN_x intermediate layers</i>	126
5.6.2	<i>SiSiC substrates with SiC intermediate layer</i>	134
5.7	FURTHER SUBSTRATES	140
5.7.1	<i>SiAlON ceramics as substrate</i>	140
5.7.2	<i>Mullite ceramics as substrate</i>	143
5.8	SUMMARY.....	145
6	SUMMARY	149
APPENDIX A	ABBREVIATIONS	153
APPENDIX B	METHODS FOR MEASUREMENT AND ANALYSIS	155
B.1	GLOW DISCHARGE MASS SPECTROSCOPY (GDMS)	155
B.2	SPECTRALLY RESOLVED LIGHT BEAM INDUCED CURRENT (SR-LBIC)	156
B.3	DEEP LEVEL TRANSIENT SPECTROSCOPY (DLTS).....	158
APPENDIX C	ELECTRICAL MODELLING OF THE SILICON SOLAR CELL	161
C.1	CURRENT/VOLTAGE CHARACTERISTICS.....	161
C.2	LOSS MECHANISMS	164
BIBLIOGRAPHY	167
ACKNOWLEDGEMENTS	180
CURRICULUM VITAE	183

List of Figures

Fig. 1.1: Cost breakdown for a commercial silicon PV module	15
Fig. 2.1: Top view of a simox cell textured by inverted pyramids.	20
Fig. 2.2: Scheme of a) backside contacted cell (upper part) and b) frontside contacted cell (lower part).	20
Fig. 2.3: Important technology paths for the different cell concepts pursued in the high temperature approach.	23
Fig. 3.1: Scheme of preparation steps to fabricate a CSiTF sample which can be processed to a CSiTF solar cell.	26
Fig. 3.2: Seeding layer on a SiO ₂ intermediate layer in different states.	30
Fig. 3.3: Degradation of solar cell efficiency with impurity concentration.	33
Fig. 3.4: Simulated diffusion of fast and slow diffusing metals out of the substrate into the epi layer during a rapid thermal CVD epitaxy	33
Fig. 4.1: Schematic of an impurity concentration profile in a CSiTF sample.	43
Fig. 4.2: Cross section of a SiSiC substrate with SiO ₂ -SiN _x -SiO ₂ intermediate layer after ZMR.	46
Fig. 4.3: Effect of transition metals on the minority carrier diffusion length in silicon.	48
Fig. 4.4: Sample structure with sole iron layer as impurity source	54
Fig. 4.5: Large area heater (LAH) with linear halogen lamps as heating elements.	55
Fig. 4.6: Structure of the samples used for the diffusion experiments	56
Fig. 4.7: Secco etched cross section of a sample treated at 1200°C for 30min.	57
Fig. 4.8: Iron concentration profiles as measured by GDMS, at two different temperatures and duration.	58
Fig. 4.9: Secco etched cross section of a sample treated at 1350°C for 30min.	58
Fig. 4.10: Sample structure with monocrystalline silicon source layer and mono- or multicrystalline silicon sink.	59
Fig. 4.11: Measured iron concentrations in the sink layer for bonded samples with SiO ₂ and SiN _x /SiO ₂ diffusion barrier, respectively.	63

-
- Fig. 4.12: Arrhenius plot of diffusion coefficient of iron in SiO₂ (left) and SiN_x (right) at different parameter values of m. 65
- Fig. 4.13: Arrhenius plot of diffusion coefficient of chromium in SiO₂ and SiN_x at different parameter values of m. 66
- Fig. 4.14: Measured vanadium concentrations in the sink layer for bonded samples with SiO₂ and SiN_x/SiO₂ diffusion barrier, respectively, as well as upper and lower limits of literature data for the solid solubility of vanadium in silicon. 67
- Fig. 4.15: Sample structure used for the diffusion experiments with ion implanted impurity source. 68
- Fig. 4.16: Comparison of vanadium profiles as simulated with SRIM and as measured by SIMS for SiO₂ (left) and SiN_x (right). 70
- Fig. 4.17: Vanadium profiles in SiO₂ measured by SIMS after different annealing times at 1000°C, 1200°C and 1350°C, respectively. 71
- Fig. 4.18: Vanadium profiles in SiN_x measured by SIMS after different annealing times at 1000°C, 1200°C and 1350°C, respectively. 72
- Fig. 4.19: Simulation with different values of the diffusion coefficient of iron calculated after DLTS analysis for SiO₂ and for SiN_x intermediate layer. 75
- Fig. 4.20: Simulation of different diffusivities in the substrate for SiO₂ and for SiN_x intermediate layer. 76
- Fig. 4.21: Simulation of iron diffusion with different values of SiO₂ intermediate layer thickness, a) for silicon substrate and b) for silicon nitride substrate. 77
- Fig. 4.22: Simulation of iron diffusion with different values of SiN_x intermediate layer thickness, a) for silicon substrate and b) for silicon nitride substrate. 78
- Fig. 5.1: Set-up of the 'old' ZMH. 82
- Fig. 5.2: Set-up of the modified zone-melting heater. 83
- Fig. 5.3: Power course of a typical ZMR process. 84
- Fig. 5.4: Process sequence of the solar cell process and resulting cell structure of CSiTF solar cells on foreign substrates. 86
- Fig. 5.5: Typical structure of subgrain boundaries. 89
- Fig. 5.6: Formation of subgrain boundaries at the inner edges of the solidification front. 89
- Fig. 5.7: Mechanism of constitutional supercooling. 90

Fig. 5.8: Relationship of ZMR parameters and width of the supercooled zone, which affect the distance between the subgrain boundaries.	92
Fig. 5.9: Lateral temperature distribution in the substrate (a) and related temperature gradient.	95
Fig. 5.10: Nomarski images of Secco-etched cross sections and polished surfaces of samples recrystallised at 910°C and 1060°C.	95
Fig. 5.11: Mean values of solar cell parameters of samples processed at different ZMR base temperature.	97
Fig. 5.12: Diffusion length topography of samples type L and M and corresponding frequency of diffusion length values.	97
Fig. 5.13: Correlation of morphology of melt zone and topography of epi layer.	99
Fig. 5.14: Surface and cross sections corresponding to the regions I and II of Fig. 5.13.	100
Fig. 5.15: Internal quantum efficiency of a textured and non-textured solar cell processed on optimised silicon layers on mc-S/SiO ₂ – substrate.	103
Fig. 5.16: Principle of the SSP manufacturing process and a sample of a SSP ribbon.	105
Fig. 5.17: Surface topography of ‘rough’ and ‘smooth’ regions of an impure SSP substrate on macroscopic and microscopic scale.	106
Fig. 5.18: Comparison of external quantum efficiency of cells with one and with two RPHP passivation steps.	108
Fig. 5.19: Effective diffusion length of samples with two RPHP treatments, but with extremely different L_{eff} values.	108
Fig. 5.20: Pictures of the melt zone during ZMR.	111
Fig. 5.21: Surface of a silicon layer on an insulating Si ₃ N ₄ ceramics without intermediate layer after ZMR..	112
Fig. 5.22: Cross sections of the solar cell DF52.1 (non-conductive substrate type A): interface and dislocated silicon layer and crack in silicon layer; excess acid has corroded the vicinity of the crack.	114
Fig. 5.23: Surface of the solar cell DF52.1: surface with clearly visible cracks and a metallisation finger which crosses a crack without causing a short circuit.	114
Fig. 5.24: Cross sections of the solar cell DF52.9 (type D): interface and dislocated silicon layer and loose Si ₃ N ₄ structure with filled pores.	115
Fig. 5.25: Typical region of the surface of the solar cell DF52.9 (type D).	116

-
- Fig. 5.26: Cross section of the solar cell DF52.11 (type B): interface with thermal SiO₂ intermediate layer and crack in the silicon layer. 117
- Fig. 5.27: Surface of the solar cell DF52.11 (type B): highly defective surface structure with cracks and crack network filled with silver. 117
- Fig. 5.28: Glow discharge mass spectroscopy of sample types A and B. 118
- Fig. 5.29: Glow discharge mass spectroscopy of sample types C and D. 119
- Fig. 5.30: Dark characteristic curves of solar cells on Si₃N₄ ceramic of type A and D after remote plasma hydrogen passivation and antireflection coating . 122
- Fig. 5.31: Integral external quantum efficiency of solar cells on samples of type A. 123
- Fig. 5.32: Mappings of the effective diffusion length of the solar cells on non-conductive ceramics (type A) and conductive ceramics (type D). 125
- Fig. 5.33: Cross section of a CSiTF sample on SiSiC substrate. 127
- Fig. 5.34: SEM image of an ONO layer on top of a SiSiC ceramics. 128
- Fig. 5.35: Impurity concentration profile of a CSiTF solar cell structure after all process steps. 128
- Fig. 5.36: CSiTF solar cells on SiSiC substrate. 130
- Fig. 5.37: Nomarski photograph of a polished and Secco etched epi layer. 131
- Fig. 5.38: Comparison of BEI and EBIC images of unpolished and polished samples. 132
- Fig. 5.39: Carrier concentration profile of the silicon layer of a thin-film solar cell on SiSiC, as obtained by spreading resistance measurement. 132
- Fig. 5.40: Diffusion length mapping of the CSiTF solar cell on SiSiC with the highest efficiency. 133
- Fig. 5.41: Absolute spectral response of the cell with maximum efficiency. 134
- Fig. 5.42: Cross section of SiSiC ceramics coated with SiC a) by LPCVD, b) by APCVD. 135
- Fig. 5.43: Cross section of a SiSiC substrate with seeding layer and epitaxial layer of good quality and with high defect density. 137
- Fig. 5.44: Top view of a zone-melting recrystallised and epitaxially thickened silicon layer on SiC intermediate layer. 137
- Fig. 5.45: Glow discharge mass spectroscopy analysis of samples with APCVD and LPCVD SiC layers. 138
- Fig. 5.46: Diffusion length topography obtained from SR-LBIC measurement of the cell with the best performance and a cell with reduced solar cell parameters. 139

Fig. 5.47: Cross section of a recrystallised silicon layer on top of a SiAlON substrate.	141
Fig. 5.48: Dark characteristics of CSiTF solar cells on SiAlON substrates.	142
Fig. 5.49: LBIC map of the best solar cell (13-1) on SiAlON substrate.	143
Fig. 5.50: Zone-melting recrystallised silicon layers on top of mullite substrates a) without and b) with ONO intermediate layer.	144
Fig. 5.51: Dark current of CSiTF solar cells on mullite substrate with and without ONO intermediate layer.	145
Fig. B.3.1: Time lapse of bias voltage and corresponding capacity change.	159
Fig. C.1.2: Geometry factor G_F at various ratios of surface to bulk recombination velocities.	163
Fig. C.1.3: Equivalent circuit of the two-diode model of a solar cell.	163